

MIDJ
in Italy

Ola H65 / H75

design Paolo Vernier, 2016

Ola stool with four legs base in white or black lacquered steel. Shell available in polypropylene, veneered wood or upholstered with leather, ecoleather, fabric, custom's fabric, hide or regenerated hide.

Ola stool is available in two different heights, and it is stackable up to 4 units.

The version with polypropylene shell is suitable for the outdoor use.



Finishing and Materials

Structure



Black Seel




White Steel

Coating




Polypropylene
8 colors



Veneered Wood Walnut



Veneered Flamed Walnut



Veneered Wood Dark Oak



Veneered wood light oak



Pix Fabric



Mirage Fabric
16 colors



Natural Wool Fabric
15 colors



Long Life Fabric
13 colors



Inca Ecoleather
17 colors



Magic Ecoleather
17 colors



Vintage Ecoleather
4 colors



Special Leather
8 colors



Fiore Leather
15 colors



Vintage Leather
4 colors



Rigenerated Hide
10 colors




Hide
19 colors



Bubble fabric
14 colors

Dimensions



Dimension	cm	inch
A	90	35.4
B	50	19.7
C	52	20.5
D	65	25.6

Volumetric Details

Weight 9.2
Volume 0.26 mc
Package 1

Gallery



Materials Certifications

Mirage Fabric	UNI EN ISO 12947, ISO 12945-2, UNI EN ISO 13934, UNI EN ISO E05-E06, EN ISO 105X12, UNI EN ISO 105 E04, EN ISO 105 B02, UNI EN ISO 105 D01, UNI EN 20105-C01, UNI 8423.
Natural Wool Fabric	CATAS N. 86473/1 25/10/07; CATAS N. 85687/1 28/09/07; BS 5852-1/79; BS 5852-1:1979
Inca Ecoleather	UNI 9175:1987
Magic Ecoleather	BS 5852-1:1979
Fiore Leather	BS 5852 parte 1; ISO 5402>50000 cicli; ISO 105B02 ? 5; ISO 3377-1 ?20 N; ISO 11644 ? 2.5 N/Cm; EN 1021/1-2; EN ISO 17233 -20°; IMO RES A 6528(16)
Vintage Leather	UNI EN ISO 105 B02 ?3; ISO 5402>50000 cicli; ISO 3377-1?20; UNI EN ISO 11640 Secco - Dry 50 c ?4 Umido - Wet 20 c ? 3; Sudore - Sweat 20 c ? 3
Bubble fabric	FIRE RETARDANT FABRIC: BS5852:2006 (p. 11 CRIB 5) EN1021-1 EN1021-2 UNI 9175:2010 - classe 1 im COMPOSITION: 100% PES MARTINDALE 35'000 CYCLES